

Sandia National Laboratories is a multimission laboratory managed and operated by National Technology and Engineering Solutions of Sandia LLC, a wholly owned subsidiary of Honeywell International Inc. for the U.S. Department of Energy's National Nuclear Security Administration under contract DE-NA0003525.

## Recent Fusion-Related Results in Drekar

Edward Phillips

Trilinos User-Developer Group Meeting 2023



Office of  
Science



U.S. DEPARTMENT OF  
**ENERGY**

Office of  
Science

*Fusion Energy Sciences*

Advances in  
Computation  
Mechanics, Austin,  
Texas, 10/22/2023

SAND#2023-11657C

# Collaborators

Jesus Bonilla and Xian-Zhu Tang, Los Alamos National Lab

Peter Ohm, RIKEN, Japan

John Shadid, Michael Crockatt, Roger Pawlowski,  
Ray Tuminaro, Jonathan Hu, Sandia National Labs

Three useful resources for fusion energy for students:



<https://www.cpepphysics.org/>


**Princeton Plasma Physics Laboratory**  
**2021 Introduction to Fusion Energy and Plasma Physics Course**  
<https://sul.i.pppl.gov/2021/course/>

**Progress toward fusion energy breakeven  
and gain as measured against the Lawson  
criterion**

Wurzel, Hsu, Physics of Plasmas 29, 062103 (2022)


## Overview of Drekar

Drekar is a finite element based multiphysics code built using Trilinos components with a strong emphasis on implicit time integration methods and linear solvers




## Motivation

- ITER Fusion conditions:
  - Temperature of  $> 100\text{M deg K}$  ( $> 6\text{x Sun core temp.}$ ).
  - Pulse times of  $\mathcal{O}(100) - \mathcal{O}(1000)$  sec. are desired. (energy confinement times of  $\mathcal{O}(1) - \mathcal{O}(10)$  sec.).
- Disruptions can cause
  - Loss of vertical positioning control.
  - Huge thermal energy deposition to the walls, and discharge of very large electrical currents to surface.
  - Huge forces can be generated in first wall & vacuum vessel structures.
- ITER can sustain only a limited number of significant disruptions,  $\mathcal{O}(1 - 5)$ .
- Understanding and controlling instabilities/disruptions in plasma confinement is critical




ITER Tokamak



Vertical Displacement Event (VDE) in ITER Tokamak Plasma and Wall Geometry (Drekar sim.)

## Goal


- Analyze macroscopic plasma **3D** behavior/instabilities under ITER conditions.



DOE Office of Science ASCR/OFES Reports: Fusion Simulation Project Workshop Report, 2007, Integrated System Modeling Workshop 2015

- Implicit** time integration (overstep fastest time scales/CFL on refined meshes).
- Stabilized FE formulation** (resolution, higher-order accuracy, enforcing constraints) (currently) Single-fluid compressible visco-resistive MHD.
- Newton-Krylov + multiphysics block preconditioners** (Highly scalable, efficient and robust solvers)

A Reduced length-scale/time scale representation; Basic single fluid  
Resistive MHD [e.g. 3D H(grad) Variational Multiscale (VMS) Stabilized FE]



Resistive MHD Model in Conservative Form

$$\frac{\partial(\rho \mathbf{v})}{\partial t} + \nabla \cdot [\rho \mathbf{v} \otimes \mathbf{v} + P \mathbf{I} - \Pi] - \mathbf{J} \times \mathbf{B} = 0$$

$$\Pi = \frac{2}{3} \mu (\nabla \cdot \mathbf{u}) \mathbf{I} + \mu [\nabla \mathbf{u} + \nabla \mathbf{u}^T]$$

Sound wave off  
diagonal coupling, and  
nearly incompressible  
flow limit ( $\nabla \cdot \mathbf{v} \approx 0$ )

$$\frac{\partial \rho}{\partial t} + \nabla \cdot (\rho \mathbf{v}) = 0$$



Alfven wave strong  
off diagonal coupling

$$\frac{\partial(\rho e)}{\partial t} + \nabla \cdot [\rho \mathbf{v} e + \mathbf{q}] - \mathbf{T} : \nabla \mathbf{v} - \eta \left\| \frac{1}{\mu_0} \nabla \times \mathbf{B} \right\|^2 = 0$$

$$\frac{\partial \mathbf{B}}{\partial t} + \nabla \cdot \left[ \mathbf{B} \otimes \mathbf{v} - \mathbf{v} \otimes \mathbf{B} - \frac{\eta}{\mu_0} (\nabla \mathbf{B} - (\nabla \mathbf{B})^T) + \psi \mathbf{I} \right] = 0$$

$$\nabla \cdot \mathbf{B} = 0$$

Elliptic constraint –  
infinite wave speed

MHD Wave speeds

$$\|\mathbf{u}\|, \|\mathbf{u}\| \pm c_s, \|\mathbf{u}\| \pm c_a, \|\mathbf{u}\| \pm c_f, \pm c_h$$

Here  $c_h$  is  $\infty$  for elliptic divergence cleaning

## Heterogeneous Multiphysics: 3D implicit unstructured FE visco-resistive MHD in ITER geometry

$$\frac{\partial \rho \mathbf{v}}{\partial t} + \nabla \cdot [\rho \mathbf{v} \otimes \mathbf{v} - (\mathbf{T} + \mathbf{T}_M)] + 2\rho \boldsymbol{\Omega} \times \mathbf{v} - \rho \mathbf{g} = \mathbf{0} \quad \mathbf{T} = - \left( P + \frac{2}{3} \mu (\nabla \cdot \mathbf{u}) \right) \mathbf{I} + \mu [\nabla \mathbf{u} + \nabla \mathbf{u}^T]$$

$$\frac{\partial \rho}{\partial t} + \nabla \cdot (\rho \mathbf{v}) = 0$$

$$\mathbf{T}_M = \frac{1}{\mu_0} \mathbf{B} \otimes \mathbf{B} - \frac{1}{2\mu_0} \|\mathbf{B}\|^2 \mathbf{I}$$

$$\frac{\partial (\rho e)}{\partial t} + \nabla \cdot [\rho \mathbf{v} e + \mathbf{q}] - \mathbf{T} : \nabla \mathbf{v} - \eta \left\| \frac{1}{\mu_0} \nabla \times \mathbf{B} \right\|^2 = 0$$

$$\frac{\partial \mathbf{B}}{\partial t} + \nabla \cdot \left[ \mathbf{B} \otimes \mathbf{v} - \mathbf{v} \otimes \mathbf{B} - \frac{\eta}{\mu_0} (\nabla \mathbf{B} - (\nabla \mathbf{B})^T) + \psi \mathbf{I} \right] = \mathbf{0}$$

$$\nabla \cdot \mathbf{B} = 0$$


Solid walls and vacuum regions

- Internal energy
- Magnetic induction

Plasma region: visco-resistive MHD

- Momentum
- Mass
- Internal energy
- Magnetic induction

- Heterogeneous Physics Regions
- Outer perfect conducting wall
  - Vacuum region
  - Solid 1<sup>st</sup> wall
  - Plasma region



# Discretization

## Finite element discretization (Galerkin terms)

Find  $\mathbf{U} \doteq [\rho, \mathbf{m}, T, \mathbf{B}, \psi]^T \in \mathcal{U}$  such that  $\rho = \bar{\rho}$  on  $\Gamma_D^\rho$ ,  $\mathbf{m} = \bar{\mathbf{m}}$  on  $\Gamma_D^{\mathbf{m}}$ ,  $T = \bar{T}$  on  $\Gamma_D^T$ ,  $\mathbf{B} = \bar{\mathbf{B}}$  on  $\Gamma_D^{\mathbf{B}}$ ,  $\psi = \bar{\psi}$  on  $\Gamma_D^\psi$ , and

$$\mathcal{A}(\mathbf{W}, \mathbf{U}) = \mathcal{F}(\mathbf{W}) \quad \forall \mathbf{W} \doteq [q, \mathbf{w}, \theta, \mathbf{C}, s]^T \in \mathcal{V},$$

where

$$\begin{aligned} \mathcal{A}(\mathbf{W}, \mathbf{U}) \doteq & (q, \partial_t \rho) - (\nabla q, \rho \mathbf{u}) \\ & + (\mathbf{w}, \partial_t \rho \mathbf{u}) - \langle \nabla \mathbf{w}, \rho \mathbf{u} \otimes \mathbf{u} \rangle - (\nabla \cdot \mathbf{w}, p + \frac{2}{3Re} (\nabla \cdot \mathbf{u})) + \langle \nabla \mathbf{w}, \frac{1}{Re} (\nabla \mathbf{u} + (\nabla \mathbf{u})^T) \rangle - (\mathbf{w}, \mathbf{j} \times \mathbf{B}) \\ & + (\theta, \partial_t T) + (\theta, \mathbf{u} \cdot \nabla T) + \frac{2}{3} (\theta, T (\nabla \cdot \mathbf{u})) + (\nabla \theta, \mathbf{q}) \\ & + (\mathbf{C}, \partial_t \mathbf{B}) - \langle \nabla \mathbf{C}, \mathbf{u} \otimes \mathbf{B} - \mathbf{B} \otimes \mathbf{u} \rangle + \left\langle \nabla \mathbf{C}, \frac{1}{S} \left( \nabla \mathbf{B} - (\nabla \mathbf{B})^T \right) \right\rangle - (\nabla \cdot \mathbf{C}, \psi) \\ & + (s, \nabla \cdot \mathbf{B}), \end{aligned}$$

$$(a, b) = \int_{\Omega} ab \, d\Omega$$

$$(\mathbf{a}, \mathbf{b}) = \int_{\Omega} \mathbf{a} \cdot \mathbf{b} \, d\Omega$$

$$\langle \mathbf{A}, \mathbf{B} \rangle = \int_{\Omega} \mathbf{A} : \mathbf{B} \, d\Omega$$

Deficiencies of Galerkin Weak Form:

- Equal-order interpolation have stability problems for saddle point prbs. (LBB condition, see .e.g. Gunzburger 1989)
  - Induction – div  $\mathbf{B} = 0$ ; Lagrange multiplier coupling  $(\mathbf{B}, \psi)$
  - Strong guide field (large  $\mathbf{B}$ ) produces an incompressible flow limit type response and a saddle point like structure (e.g. Stokes-like behavior for  $(\rho \mathbf{u}, \rho)$ )
- Strong convective transport and large unresolved gradients can produce unphysical spatial oscillations (internal / boundary layers).
- For unresolved high-wavenumber signals aliasing of energy into lower-wavenumber resolved components

# Brief Outline Following Variational Multiscale (VMS) Approach

VMS: T.J.R Hughes et. al.; & VMS MHD: Codina et. al., JS et. al.

## Upwinding and saddle point stabilization

Let us split the solution and test spaces in resolved and unresolved scales, i.e.,  $\mathcal{U} = \mathcal{U}_h + \mathcal{U}'$  and  $\mathcal{V} = \mathcal{V}_h + \mathcal{V}'$ . thus we have

$$\begin{aligned} \mathcal{A}(\mathbf{W}_h, \mathbf{U}_h + \mathbf{U}') &= \mathcal{F}(\mathbf{W}_h) \quad \forall \mathbf{W}_h \in \mathcal{V}_h \\ \mathcal{A}(\mathbf{W}', \mathbf{U}_h + \mathbf{U}') &= \mathcal{F}(\mathbf{W}') \quad \forall \mathbf{W}' \in \mathcal{V}' \end{aligned} \rightarrow \mathbf{U}' \text{ not resolved, modeled by } \mathbf{U}' \approx -\tau \mathbf{P}\mathcal{R}(\mathbf{U}^h)$$

*i.e. sub-grid / unresolved scales driven by residual resolved scales of strong from PDEs, variationally consistent*

VMS + additional optional DCO terms are included for enhanced stability

$$\begin{aligned} \mathcal{A}(\mathbf{W}_h, \mathbf{U}_h + \mathbf{U}') &= \mathcal{A}(\mathbf{W}_h, \mathbf{U}_h) - \sum_{K \in \mathcal{T}_h} \left( (\nabla q_h, \rho_h \mathbf{u}' + \mathbf{u}_h \rho')_K \right. \\ &\quad + \langle \nabla \mathbf{w}_h, \rho \mathbf{u}' \otimes \mathbf{u}_h + \rho' \mathbf{u}_h \otimes \mathbf{u}_h \rangle_K + (\nabla \cdot \mathbf{w}_h, p')_K \\ &\quad + (\nabla \theta_h, \mathbf{u}_h T')_K \\ &\quad + \langle \nabla \mathbf{C}_h, \mathbf{u}_h \otimes \mathbf{B}' - \mathbf{B}' \otimes \mathbf{u}_h \rangle_K + (\nabla \cdot \mathbf{C}_h, \psi')_K \\ &\quad + (\nabla s_h, \mathbf{B}')_K \\ &\quad + (\nabla q_h, \nu_\rho^K \nabla \rho_h)_K \\ &\quad + (\nabla \mathbf{w}_h, \frac{1}{2} \nu_m^K (\nabla \mathbf{u}_h + (\nabla \mathbf{u}_h)^T))_K + \langle \nabla \mathbf{w}_h, \nu_\rho^K \nabla \rho_h \otimes \mathbf{u}_h \rangle_K \\ &\quad \left. + \frac{C}{2} (u_A h \hat{b} \cdot \nabla \theta, \hat{b} \cdot \nabla T)_K \right) \end{aligned}$$

VMS

DCO LLF [density]

DCO R(s) [momentum]

$\hat{b}$  DCO [temperature]

**First order** cG finite elements for  $\rho_h, \mathbf{m}_h, \mathbf{B}_h, \psi_h$  and **second order** finite elements  $T_h$ .


Bonilla, S, Tang, Crockatt, Ohm, Phillips, Pawlowski, Conde, Beznosov, On a Fully-implicit VMS-stabilized FE Formulation for Low Mach Number Compressible Resistive MHD with Application to MCF, Comput. Methods Appl. Mech. Engrg. 2023

S, Pawlowski, Cyr, Tuminaro, Chacon, Weber, Scalable Implicit Incompressible Resistive MHD with Stabilized FE and Fully-coupled Newton-Krylov-AMG, Comput. Methods Appl. Mech. Engrg. 304, 1–25, 2016

# **Preliminary Results**

**Vertical displacement events (VDEs) are major disruption events occurring in tokamaks when vertical stability control is lost.**

These events cause large currents to flow in the vessel and other adjacent metallic structures.




1. Cold VDE, Thermal Quench – a fast internal energy loss (i.e. Temperature drop)
  1. Initial equilibrium force balance is lost:  $(\mathbf{J} \times \mathbf{B})_{0+} \neq (\nabla P)_{0+}$
  2. Loss of vertical position control
2. Temperature drop => resistivity increases => plasma current drops + ohmic to runaway electron current conversion.
3. Plasma current drop, new sequence of quasi-steady "equilibriums" => magnetic field rearrangement. i.e. VDE
4. VDE => large halo currents produced in walls and large EM forces

## Vertical Displacement Event (VDE) II

### Parameters

- $D_2$  plasma
- $B_0 : 5T$
- $T : 40 \text{ keV } (> 100M \text{ K})$
- $n : 10^{20}$
- $S_p : 10^4 - 10^7$  (Scaling results up to  $10^{10}$ )
- $S_w : 10^4$
- $S_{vv} : 10^5$
- $\kappa_{\perp} : 10^{-3}$  (thermal quench)
- $\nu : 10^{-2}$




## Internal kink


- Initial equilibrium with  $q$  profile  $< 0.9$  (very unstable)
- Introduced (1,1) perturbation and let evolve in time
  - (1,1) leads to sawtooth crash with island growth
  - (2,1) is excited leading to stochastic magnetic field
  - breakdown of magnetic surfaces and a disruption.

- $B_0 : 5T$
- $n : 10^{20}$
- $Sp : 10^4 - 10^6$

- $\kappa_{\perp} : 10^{-5}$
- $\kappa_{\parallel} : 10^{-3}$
- $\nu : 10^{-5}$



Return map of B to  
Poloidal plane:  
Poincare Plot t=8498.214007



Physics-based and Approximate Block Factorizations: Coercing **Strongly Coupled Off- Diagonal Physics and/or Disparate Discretizations and Scalable Multigrid** to play well together

$$\frac{\partial u}{\partial t} = \frac{\partial v}{\partial x}, \quad \frac{\partial v}{\partial t} = \frac{\partial u}{\partial x}$$

Semi-discrete in time (e.g. BE):

Eliminate variable to parabolic form

$$u^{n+1} = u^n + \Delta t \frac{\partial v^{n+1}}{\partial x}, \quad v^{n+1} = v^n + \Delta t \frac{\partial u^{n+1}}{\partial x}$$

$$\frac{u^{n+1} - u^n}{\Delta t} - \Delta t \frac{\partial^2 u^{n+1}}{\partial x^2} = \frac{\partial v^n}{\partial x}$$

The resulting equation

$$(I - \Delta t^2 \mathcal{L}_{xx}) u^{n+1} = \mathcal{F}^n$$

Semi-discrete in time:

Approximate Block Factorizations & Schur-complements:

$$\begin{bmatrix} I & -\Delta t C_x \\ -\Delta t C_x & I \end{bmatrix} \begin{bmatrix} u^{n+1} \\ v^{n+1} \end{bmatrix} = \begin{bmatrix} u^n - \Delta t C_x v^n \\ v^n - \Delta t C_x u^n \end{bmatrix}$$

$$\begin{bmatrix} D_1 & U \\ L & D_2 \end{bmatrix} = \begin{bmatrix} I & U D_2^{-1} \\ 0 & I \end{bmatrix} \begin{bmatrix} D_1 - U D_2^{-1} L & 0 \\ 0 & D_2 \end{bmatrix} \begin{bmatrix} I & 0 \\ D_2^{-1} L & I \end{bmatrix}$$

The Schur complement is then

$$D_1 - U D_2^{-1} L = (I - \Delta t^2 C_x C_x) \approx (I - \Delta t^2 \mathcal{L}_{xx})$$

**Recall: This is motivating how we develop preconditioners, not for developing solvers. The NK method still seeks the solution to the original nonlinear/linear system residual!**

[w/ L. Chacon (LANL) ]

---


$$[\mathbf{F}_{\text{ns}} = [\mathbf{F}_{\rho\mathbf{u}}, \mathbf{F}_{\rho}], \mathbf{F}_{\mathbf{B}}, \mathbf{L}_{\mathbf{r}}, F_T]$$

Block Jacobi

$$\begin{bmatrix} \mathbf{F}_{\text{ns}} & \mathbf{Z} & & C_T \\ \mathbf{Y} & \mathbf{F}_{\mathbf{B}} & \mathcal{B}_{\mathbf{B}}^T & \\ \mathbf{C}_{\text{ns}} & \mathcal{B}_{\mathbf{B}} & \mathbf{L}_{\mathbf{r}} & \\ A_T & \mathbf{Z}_T & & F_T \end{bmatrix}^{-1}$$

---

|                                                                                                                                                      |                |
|------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|
| $[\mathbf{F}_{\text{ns}} = [\mathbf{F}_{\rho\mathbf{u}}, \mathbf{F}_{\rho}], \mathbf{F}_{\mathbf{B}}, \mathbf{L}_{\mathbf{r}}, F_T]$<br>Block Jacobi |                |
| $[\mathbf{F}_{\text{ns}}, \mathbf{F}_{\mathbf{B}}, \mathbf{L}_{\mathbf{r}}]$<br>Operator Splitting                                                   | $[F_T]$<br>AMG |

$$\left[ \begin{bmatrix} \mathbf{F}_{\text{ns}} & \mathbf{Z} \\ \mathbf{Y} & \mathbf{F}_{\mathbf{B}} & \mathcal{B}_{\mathbf{B}}^T \\ \mathbf{C}_{\text{ns}} & \mathcal{B}_{\mathbf{B}} & \mathbf{L}_{\mathbf{r}} \end{bmatrix}^{-1} \quad \right] [F_T]^{-1}$$

---

|                                                                                                                                                      |                                                                             |                |
|------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|----------------|
| $[\mathbf{F}_{\text{ns}} = [\mathbf{F}_{\rho\mathbf{u}}, \mathbf{F}_{\rho}], \mathbf{F}_{\mathbf{B}}, \mathbf{L}_{\mathbf{r}}, F_T]$<br>Block Jacobi |                                                                             |                |
| $[\mathbf{F}_{\text{ns}}, \mathbf{F}_{\mathbf{B}}, \mathbf{L}_{\mathbf{r}}]$<br>Operator Splitting                                                   |                                                                             | $[F_T]$<br>AMG |
| $[\mathbf{F}_{\mathbf{B}}, \mathbf{L}_{\mathbf{r}}]$<br>LU Decomp. + SIMPLEC                                                                         | $[\mathbf{F}_{\mathbf{B}}, \mathbf{F}_{\text{ns}}]$<br>LU Decomp. + SIMPLEC |                |

$$\left( \begin{bmatrix} \mathbf{F}_{\text{ns}} & \mathbf{Z} \\ \mathbf{Y} & \mathbf{F}_{\mathbf{B}} \end{bmatrix} \begin{bmatrix} \mathbf{I} & & \\ & \mathbf{F}_{\mathbf{B}}^{-1} & \\ \mathbf{C}_{\text{ns}} & & \mathbf{I} \end{bmatrix} \begin{bmatrix} \mathbf{I} & & \\ & \mathbf{F}_{\mathbf{B}} & \mathcal{B}_{\mathbf{B}}^T \\ & \mathcal{B}_{\mathbf{B}} & \mathbf{L}_{\mathbf{r}} \end{bmatrix} \right)^{-1}$$

2x2 critical implicit Stiff Alfven wave coupling

2x2 Saddle point system for (B,r)

|                                                                                                                                              |                         |                                                                             |                                                    |
|----------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|-----------------------------------------------------------------------------|----------------------------------------------------|
| $[\mathbf{F}_{\text{ns}} = [\mathbf{F}_{\rho u}, \mathbf{F}_{\rho}], \mathbf{F}_{\mathbf{B}}, \mathbf{L}_{\mathbf{r}}, F_T]$<br>Block Jacobi |                         |                                                                             |                                                    |
| $[\mathbf{F}_{\text{ns}}, \mathbf{F}_{\mathbf{B}}, \mathbf{L}_{\mathbf{r}}]$<br>Operator Splitting                                           |                         |                                                                             | $[\mathbf{F}_T]$<br>AMG                            |
| $[\mathbf{F}_{\mathbf{B}}, \mathbf{L}_{\mathbf{r}}]$<br>LU Decomp. + SIMPLEC                                                                 |                         | $[\mathbf{F}_{\mathbf{B}}, \mathbf{F}_{\text{ns}}]$<br>LU Decomp. + SIMPLEC |                                                    |
| $[\mathbf{F}_{\mathbf{B}}]$<br>AMG                                                                                                           | $[\mathbf{S}_L]$<br>AMG | $[\mathbf{S}_{\text{mag}}]$<br>AMG                                          | $[\mathbf{F}_{\text{ns}}]$<br>LU Decomp. + SIMPLEC |

$$\begin{bmatrix} \mathbf{I} & & \\ & \mathbf{F}_{\mathbf{B}} & \mathcal{B}_{\mathbf{B}}^T \\ & & \mathbf{S}_L \end{bmatrix}^{-1} \begin{bmatrix} \mathbf{I} & & \\ & \mathbf{F}_{\mathbf{B}} & \\ & -\mathcal{B}_{\mathbf{B}} & \mathbf{I} \end{bmatrix}, \quad \begin{bmatrix} \mathbf{F}_{\text{ns}} & \mathbf{Z} \\ & \mathbf{S}_{\text{mag}} \\ & & \mathbf{I} \end{bmatrix}^{-1} \begin{bmatrix} \mathbf{I} & & \\ -\mathbf{Y} \mathbf{F}_{\text{ns}}^{-1} & \mathbf{I} & \\ & & \mathbf{I} \end{bmatrix}$$

$$\mathbf{S}_L := \mathbf{L}_{\mathbf{r}} - \mathcal{B}_{\mathbf{B}}(\text{absrowsum}(\mathbf{F}_{\mathbf{B}}))^{-1} \mathcal{B}_{\mathbf{B}}^T, \quad \mathbf{S}_{\text{mag}} := \mathbf{F}_{\mathbf{B}} - \mathbf{Y}(\text{absrowsum}(\mathbf{F}_{\text{ns}}))^{-1} \mathbf{Z}$$


$$\mathbf{F}_{ns} = \begin{bmatrix} \mathbf{F}_{\rho u} & \mathbf{B}_{\rho u, \rho}^T \\ \mathbf{B}_{\rho, \rho u} & \mathbf{F}_{\rho} \end{bmatrix}$$

---

|                                                                                                                                                      |                         |                                                                             |                                                    |                              |                |
|------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------|-----------------------------------------------------------------------------|----------------------------------------------------|------------------------------|----------------|
| $[\mathbf{F}_{\text{ns}} = [\mathbf{F}_{\rho\mathbf{u}}, \mathbf{F}_{\rho}], \mathbf{F}_{\mathbf{B}}, \mathbf{L}_{\mathbf{r}}, F_T]$<br>Block Jacobi |                         |                                                                             |                                                    |                              |                |
| $[\mathbf{F}_{\text{ns}}, \mathbf{F}_{\mathbf{B}}, \mathbf{L}_{\mathbf{r}}]$<br>Operator Splitting                                                   |                         |                                                                             |                                                    |                              | $[F_T]$<br>AMG |
| $[\mathbf{F}_{\mathbf{B}}, \mathbf{L}_{\mathbf{r}}]$<br>LU Decomp. + SIMPLEC                                                                         |                         | $[\mathbf{F}_{\mathbf{B}}, \mathbf{F}_{\text{ns}}]$<br>LU Decomp. + SIMPLEC |                                                    |                              |                |
| $[\mathbf{F}_{\mathbf{B}}]$<br>AMG                                                                                                                   | $[\mathbf{S}_L]$<br>AMG | $[\mathbf{S}_{\text{mag}}]$<br>AMG                                          | $[\mathbf{F}_{\text{ns}}]$<br>LU Decomp. + SIMPLEC |                              |                |
|                                                                                                                                                      |                         |                                                                             | $[\mathbf{F}_{\mathbf{u}}]$<br>AMG                 | $[\mathbf{S}_{\rho}]$<br>AMG |                |

$$\mathbf{F}_{\text{ns}} \approx \mathcal{M}_{NS} = \begin{bmatrix} \mathbf{F}_{\rho\mathbf{u}} & \tilde{\mathbf{B}}_{\rho\mathbf{u},\rho}^T \\ & \mathbf{S}_{\rho} \end{bmatrix}$$

$$\mathbf{S}_{\rho} = \mathbf{F}_{\rho} - \mathbf{B}_{\rho,\rho\mathbf{u}}(\text{absrowsum}(\mathbf{F}_{\rho\mathbf{u}}))^{-1} \tilde{\mathbf{B}}_{\rho\mathbf{u},\rho}^T$$



(B,r) saddle point problem  
for  $\nabla \cdot \mathbf{B} = 0$

Stiff Alfven  
Wave Coupling

Nearly incompressible flow  
saddle point problem  
 $\nabla \cdot \mathbf{u} \approx 0$

# Drekar Strong Scaling Results 3D ITER VDE





Strong scaling unperturbed initial equilibrium on coarse mesh with  $S = 1e4$ .

To 250 global Alfvén times. 72 cores  $\rightarrow$  4608 cores (64x increase).


Coarse Mesh 0: 347K elements, 7.2K poloidal x 48 toroidal

Constant time-step size  $dt = 2$


Max  $CFL_A \sim 750$ ,  $CFL_u \sim 3.2$



# Drekar Weak scaling Study 3D ITER VDE



mesh 0. : 347K elements, 7.2K poloidal x 48 toroidal,  $dt \sim 1.2$ ; 108 cores on ghost  
 mesh 1. : 2.77M elements, 28.8K poloidal x 96 toroidal,  $dt \sim 0.55$ ; 864 cores on ghost  
 mesh 2. : 22.2M elements, 115.2K poloidal x 192 toroidal,  $dt \sim 0.25$ ; 6912 cores on ghost





Unstructured  
mesh sequence

To 50 global Alfvén times  
 Max  $CFL_A = 400$ ,  $CFL_u = 2$

$Pr_m = 0.1$ ,  $Pr_T = 1$

# Lundquist Number scaling, coarse mesh 0.5 to 25 global Alfven times.

( $Pr_m = 10$ ,  $Pr_T = 1$  i.e. both momentum and thermal diffusivities the same, scale 10x resistivity )






Mesh 0.5:  
1.28M elements, 10K  
poloidal x 128  
toroidal, 1120 ARM  
cores

To 25 global Alfven times  
Max  $CFL_A = 400$ ,  $CFL_u = 2$   
 $dt \sim 1.0$

# Time-step Size scaling for $S = 10^7$

Coarse mesh0



To 100 global Alfven times

## Conclusions

- Developed scalable fully implicit low Mach compressible visco-resistive MHD solver.
  - Stabilized FE formulation → definite linear system and solvability (demonstrated numerically)
  - Approximate block factorization → scalable treatment of multiphysics equation coupling.
  - Scalable AMG solves → efficient scalable sub-block preconditioning.
- Demonstrated scalability (strong and weak), Lundquist number robustness, promising initial efficiency for longer-time scale simulations.
- Proof-of-principle numerical experiments.
  - Cold VDE.
  - (1,1) internal kink mode.
- Future work
  - Further V&V benchmarks.
  - Extension to two temperature models ( $T_i$ ,  $T_e$ ).


## Tokamak Disruption Simulation (TDS) SciDAC Center



Tokamak Disruption  
Simulation (TDS) SciDAC  
center

DOE Office of Science  
ASCR/OFES SciDAC-4 Partnership (FY18 – FY23)

## Ten TDS partner institutions



Xianzhu Tang (Lead – DOE PI, LANL PI)  
J Shadid (DOE ASCR – PI, SNL PI)